



Midea Energy



# Aqua-C2.5S 2089-500-4h IEC G2 Liquid-Cooled Energy Storage System

## Optimal Costs

- 10-foot design, weighing less than 23 tons, enabling easy transportation and deployment in confined spaces.
- Integrated AC/DC bi-directional inverter, reducing commissioning time.

## Capacity Enhancement

- Modular design reduces failure impacts and improves system uptime.
- Active balancing technology and bio-inspired solutions enhance battery lifespan and system discharge capacity.

## Ultimate Security

- Multi-level electrical protection, fire protection, arc flash analysis, and collaborative protection.
- Intelligent management of battery health for early warning of faulty batteries.
- Compliant with IEEE 693 high seismic level.

## Convenient O&M

- Active balancing technology reduces O&M costs for energy storage stations.
- Rapid state detection and fault recording achieve rapid positioning and analysis of system faults.

Parameter	Aqua-C2.5S 2089-500-4h IEC G2
<b>DC-side parameter</b>	
Cell type	LFP 3.2 V/314 Ah
Battery configuration	5P416S
Nominal energy	2089 kWh
Battery voltage range	1081.6–1497.6 V
Nominal battery voltage	1331.2 V
<b>AC-side parameter</b>	
Nominal power	500 kVA
Maximum THD of current	< 3% (at nominal power)
DC component	< 0.5%
Nominal voltage	550 V
AC voltage range	495–605 V (< 498 V derating)
Nominal frequency	50 Hz/60 Hz
Maximum current	580 A × 3 phases
Power factor	≥ 0.99 (at nominal power)
Power factor range	–1 to +1
<b>System parameter</b>	
Operating ambient temperature range	–30°C to +50°C (> 45°C derating)
Relative humidity	≤ 100% RH (non-condensing)
Maximum operating altitude	3000 m
Ingress protection (IP) rating	IP66
Cooling method	Intelligent liquid cooling
Noise	≤ 75 dB (@ 1 m, ambient temperature 35°C)
Weight	≤ 23000 kg
Anti-corrosion degree	<ul style="list-style-type: none"> <li>● C4</li> <li>● C5 (optional)</li> </ul>
Seismic level	IEEE 693 high seismic level qualification
Snow load	1.44 kPa
Wind load	57.7 m/s
Dimensions (W × D × H)	3126 mm × 2438 mm × 2896 mm
Fire suppression system	Fire control alarm panel, smoke and heat detectors, alarm bell, horn strobe, gas detector, ventilation system (compliant with NFPA 69), dry pipes with sprinklers, aerosol
Communication interface	Ethernet
Communication protocol	Modbus-TCP, IEC 104, IEC 61850
Standard compliance	IEC 62933-5-2, IEC 61000, IEC 62619, IEC 63056, IEC 62477-1, JETGR0004-1-2.1, JETGR0005-1-1.0, JEAC9701-2024, JC-STAR, EN 50549



Midea Energy



# Aqua-C2.5S 2508-600-4h IEC G2 Liquid-Cooled Energy Storage System

## Optimal Costs

- 10-foot design, weighing less than 25 tons, enabling easy transportation and deployment in confined spaces.
- Integrated AC/DC bi-directional inverter, reducing commissioning time.

## Capacity Enhancement

- Modular design reduces failure impacts and improves system uptime.
- Active balancing technology and bio-inspired solutions enhance battery lifespan and system discharge capacity.

## Ultimate Security

- Multi-level electrical protection, fire protection, arc flash analysis, and collaborative protection.
- Intelligent management of battery health for early warning of faulty batteries.
- Compliant with IEEE 693 high seismic level.

## Convenient O&M

- Active balancing technology reduces O&M costs for energy storage stations.
- Rapid state detection and fault recording achieve rapid positioning and analysis of system faults.

Parameter	Aqua-C2.5S 2508-600-4h IEC G2
<b>DC-side parameter</b>	
Cell type	LFP 3.2 V/314 Ah
Battery configuration	6P416S
Nominal energy	2508 kWh
Battery voltage range	1081.6–1497.6 V
Nominal battery voltage	1331.2 V
<b>AC-side parameter</b>	
Nominal power	600 kVA
Maximum THD of current	< 3% (at nominal power)
DC component	< 0.5%
Nominal voltage	550 V
AC voltage range	495–605 V (< 498 V derating)
Nominal frequency	50 Hz/60 Hz
Maximum current	630 A × 3 phases
Power factor	≥ 0.99 (at nominal power)
Power factor range	–1 to +1
<b>System parameter</b>	
Operating ambient temperature range	–30°C to +50°C (> 45°C derating)
Relative humidity	≤ 100% RH (non-condensing)
Maximum operating altitude	3000 m
Ingress protection (IP) rating	IP66
Cooling method	Intelligent liquid cooling
Noise	≤ 75 dB (@ 1 m, ambient temperature 35°C)
Weight	≤ 25000 kg
Anti-corrosion degree	<ul style="list-style-type: none"> <li>● C4</li> <li>● C5 (optional)</li> </ul>
Seismic level	IEEE 693 high seismic level qualification
Snow load	1.44 kPa
Wind load	57.7 m/s
Dimensions (W × D × H)	3126 mm × 2438 mm × 2896 mm
Fire suppression system	Fire control alarm panel, smoke and heat detectors, alarm bell, horn strobe, gas detector, ventilation system (compliant with NFPA 69), dry pipes with sprinklers, aerosol
Communication interface	Ethernet
Communication protocol	Modbus-TCP, IEC 104, IEC 61850
Standard compliance	IEC 62933-5-2, IEC 61000, IEC 62619, IEC 63056, IEC 62477-1, JETGR0004-1-2.1, JETGR0005-1-1.0, JEAC9701-2024, JC-STAR