

Aqua C2.5S-2089-500-4h

Liquid-cooled Energy Storage System



* The illustration is for reference only. The actual product's appearance might vary depending on the configurations.



Optimal Costs

- 10-foot design, weighing less than 20 tons, enabling easy transportation and deployment in confined spaces
- Integrated AC/DC bi-directional inverter, reducing commissioning time



Ultimate Security

- Multi-level electrical protection, fire protection, arc flash analysis, and collaborative protection
- Intelligent management of battery health for early warning of faulty batteries
- Compliant with IEEE 693 high seismic level



Capacity Enhancement

- Modular design reduces failure impacts and improves system uptime.
- Active balancing technology and bio-inspired solutions enhance battery lifespan and system discharge capacity.



Convenient O&M

- Active balancing technology reduces O&M costs for energy storage stations.
- Rapid state detection and fault recording achieve rapid positioning and analysis of system faults.

| Model | Aqua C2.5S-2089-500-4h |
|-------------------------------------|--|
| DC-side parameter | |
| Cell type | LFP 3.2 V/314 Ah |
| Battery configuration | 5P416S |
| Nominal energy | 2089 kWh |
| Battery voltage range | 1123.2–1497.6 V |
| Nominal battery voltage | 1331.2 V |
| AC-side parameter | |
| Nominal power | 500 kVA |
| Maximum THD of current | < 3% (at nominal power) |
| DC component | < 0.5% |
| Nominal voltage | 690 V |
| AC voltage range | 621–759 V |
| Nominal frequency | 50 Hz/60 Hz |
| Rated current | 418.4 A × 3 phases (capable of continuous operation at 110% of rated current) |
| Power factor | ≥ 0.99 (at nominal power) |
| Power factor range | –1 to +1 |
| System parameter | |
| Operating ambient temperature range | –30°C to +50°C (> 45°C derating) |
| Relative humidity | ≤ 100% RH (non-condensing) |
| Maximum operating altitude | 2000 m |
| Ingress protection (IP) rating | IP55 |
| Cooling method | Intelligent liquid cooling |
| Noise | ≤ 75 dB (@ 1 m, ambient temperature 35°C) |
| Weight | ≤ 20000 kg |
| Anti-corrosion degree | C4 C5 (optional) |
| Seismic level | IEEE 693 high seismic level qualification |
| Snow load | 30 lb/sqft |
| Wind load | 129 mph |
| Dimension (W × D × H) | 2991 mm × 2438 mm × 2896 mm |
| Fire suppression system | Fire control alarm panel, smoke and heat detectors, alarm bell, horn strobe, gas detector, ventilation system (compliant with NFPA 69), dry pipes with sprinklers, aerosol |
| Communication interface | Ethernet |
| Communication protocol | Modbus-TCP, IEC 104, IEC 61850 |
| Standard compliance | IEC 62933-5-2, IEC 61000, IEC 62619, IEC 63056, IEC 62477-1, JETGR0004-1-2.1, JETGR0005-1-1.0, JEM_1505, JEAC9701-2024 |